

STANLEY® FatMax® TruLaser™ Comparison Chart --- LaserStreet.com

Technical Data	TLM 100	TLM 200	TLM 300
Measuring Accuracy	± 1/4 in (± 6mm)	± 1/8 th in (± 3mm)	± 3/32 nd in (± 2mm)
Range	2ft - 100ft (0.6 - 30m)	1ft - 100ft (0.3 - 30m)	2in - 650ft (0.05 - 200m)
Units of Measure	Metric, ft 1/8 th in, ft/100ths, in/10ths	Metric, ft 1/16 th in, ft/100ths, in/10ths	Metric, ft 1/32 nd in, ft/100ths, in/10ths
Laser Class, Type	Class IIIA, 630-690 nm	Class 2M, 635 nm	Class 2M, 635 nm
Distance, Area, Volume Calculations	•	•	•
Addition & Subtraction	•	•	•
Continuous Measuring (tracking)		•	•
Min/Max Distance Tracking		•	•
Indirect Height/Length		Pythagoras Function: 2-Point	Pythagoras Function: 2-Point, 3-Point
Built-in Telescopic 2X Viewer			•
Built-in Bubble Level			•
Time Delay Release			•
Universal Tripod Mount			•
Splash proof/ Dust proof (IP 54)		•	•
Multifunction End Piece			•
Backlit Display		•	•
Memory Storage			20 Values
Measuring Reference	Front, Rear	Front, Rear	Front, Rear, Tripod, End Piece
Keyboard Type	Rubber	Foil Keypad	Soft-Touch
Wrist Strap			•
Holster w/Belt Loop	•	•	•
Operating Temperature	+41°F to +122F (+5°C to +50C)	-14°F to +122F (-10°C to +50C)	-14°F to +122F (-10°C to +50C)
Storage Temperature	-22°F to +158F (-30°C to +70C)	-13°F to +158F (-25°C to +70C)	-13°F to +158F (-25°C to +70C)
Battery Life (no. of measurements)	up to 2,000	up to 5,000	up to 10,000
Battery Type (Qty)	9V (1)	AAA (2)	AA (2)
Manufacturer's Warranty	1 Year	1 Year	2 Years
List Price	\$99.00	\$249.00	\$449.00